



EL2889 | HD EtherCAT Terminal, 16-channel digital output 24 V DC, 0.5 A, 0 V (ground) switching

The EL2889 digital output terminal connects the binary control signals from the automation device on to the actuators at the process level with electrical isolation. The EL2889 is protected against polarity reversal and processes load currents with outputs protected against overload and short-circuit. The EtherCAT Terminal contains 16 channels, whose signal states are displayed by LEDs. The terminal is particularly suitable for space-saving use in control cabinets. The connection technology is particularly suitable for single-ended inputs. All components have to use the same reference point as the EL2889. The power contacts are looped through.

The outputs are fed via the 0 V power contact in the EL2889. The conductors can be connected without tools in the case of solid wires using a direct plug-in technique.

The HD EtherCAT Terminals (High Density) with increased packing density feature 16 connection points in the housing of a 12 mm terminal block.

Technical data	EL2889
Connection technology	1-wire
Number of outputs	16
Rated load voltage	24 V DC (-15 %/+20 %)
Load type	ohmic, inductive, lamp load
Distributed clocks	–
Max. output current	0.5 A (short-circuit-proof) per channel
Short circuit current	typ. < 7 A
Reverse voltage protection	yes
Breaking energy	< 100 mJ/channel
Switching times	T _{ON} : 50 µs, T _{OFF} : 200 µs
Current consumption E-bus	typ. 140 mA
Electrical isolation	500 V (E-bus/field potential)
Current consumption power contacts	typ. 30 mA + load
Bit width in the process image	16 outputs
Configuration	no address or configuration setting
Conductor types	solid wire, stranded wire and ferrule
Conductor connection	solid wire conductors: direct plug-in technique; stranded wire conductors and ferrules: spring actuation by screwdriver
Rated cross-section	solid wire: 0.08...1.5 mm ² ; stranded wire: 0.25...1.5 mm ² ; ferrule: 0.14...0.75 mm ²
Weight	approx. 70 g
Operating/storage temperature	-25...+60 °C/-40...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Approvals	CE, UL, Ex