



CP2E-N20DT-D

CP2E series compact PLC - Network type; 12 DI, 8DO; NPN output; Power supply 24 VDC; 10 kStep Program memory

Specifications

Supply voltage type	DC
Input type	PNP/NPN
Number of digital inputs	12
Output type	NPN
Number of digital outputs	8
Program capacity	20 K steps
Data memory capacity	16 K words
Logic execution time	0.23 μ s
Communication port(s)	Ethernet TCP/IP
Number of Ethernet ports	1
Number of USB ports	0
Number of RS-232 ports	0
Number of RS-485 ports	0
Communication option(s)	Serial RS-232C, Serial RS-422, Serial RS-485
Number of encoder input channels	6
Max. encoder input frequency	100 kHz
Max. number of PTP axes	2
Max. pulse output frequency	100 kHz
Function Block programming	✓
Battery-free memory backup	✓
Real-time clock	✓
Analogue option boards	✓
Max. number of analogue I/O channels	4

Max. number of local I/O points	20
Max. number of expansion units	0
Built-in auxiliary 24 VDC output	0 mA
Operating temperature range	-20-60 °C
Product Height (unpacked)	90 mm
Product Width (unpacked)	86 mm
Product Depth (unpacked)	80 mm

Accessories



CP1W-ADB21

I/O option board (only CP1L-EL/EM port 1 or 2), 2 x analog inputs 0 to 10 V, resolution 1/4000 or 0 to 20 mA, resolution 1:2000



CP1W-CIF01

CP1 RS-232C (15 m max.) serial communication option board



CP1W-CIF11

CP1 RS422/485 (50 m max.) serial communication option board



CP1W-CIF12-V1

CP1 RS422/485 (isolated 500 m max.) serial communication option board



CP1W-CIF41

CP1 Ethernet communications option, 1 x RJ45 socket



CP1W-DAB21V

I/O option board (only CP1L-EL/EM port 1 or 2), 2 x analog outputs 0 to 10 V, resolution 1:4000



CP1W-MAB221

I/O option board (only CP1L-EL/EM port 1 or 2), 2 x analog inputs 0 to 10 V, resolution 1:4000 or 0 to 20 mA, resolution 1:2000, 2 x analog outputs 0 to 10 V, resolution 1:4000



CP2W-CIFD1

CP2-series Serial Option board 2 x RS-232 ports



CP2W-CIFD2

CP2-series Serial Option board 1 x RS-232, 1 x RS-485 ports



CP2W-CIFD3

CP2-series Serial Option board 2 x RS-485 ports



CXONE-LT01-EV4

CX-One Lite v4.x software, for Windows 2000/XP/Vista, single-user licence only, (requires CDs, CXOne-LTCD-EV4), limited to program the CPx PLC platform



XS6W-6LSZH8SS200CM-B

Ethernet patch cable, F/UTP, Cat.6A, LSZH (Blue), 2 m



XS6W-6LSZH8SS300CM-B

Ethernet patch cable, F/UTP, Cat.6A, LSZH (Blue), 3 m

Downloads

CAD Library



CP1E/CP2E CPU Unit Instructions Reference Manual

EN PDF 9.96 MB



CP2E Brochure

EN PDF 2.44 MB



CP2E Datasheet

EN PDF 8.66 MB




CP2E Hardware Users Manual

EN PDF 24.5 MB



CP2E Software Users Manual

EN PDF 36 MB



NB Faceplate 3.0 - Multilanguage Software

EN ZIP 79.7 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 21 August, 2023. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU