## 6GK5108-0BA00-2AC2

**Data sheet** 



SCALANCE XC108, Unmanaged IE switch, 8x 10/100 Mbit/s RJ45 ports, LED diagnostics, error-signaling contact with set pushbutton, redundant power supply Manual available as a download.

product type designation	SCALANCE XC108	
transfer rate		
transfer rate	10 Mbit/s, 100 Mbit/s	
interfaces / for communication / maximum configuration for modular devices		
number of electrical ports / maximum	8	
interfaces / for communication / integrated		
number of electrical connections		
<ul> <li>for network components or terminal equipment</li> </ul>	8; RJ45	
interfaces / other		
number of electrical connections		
for signaling contact	1	
<ul><li>for power supply</li></ul>	1	
type of electrical connection		
<ul> <li>for signaling contact</li> </ul>	2-pole terminal block	
<ul><li>for power supply</li></ul>	4-pole terminal block	
signal inputs/outputs		
operating voltage / of the signaling contacts		
at DC / rated value	24 V	
operational current / of the signaling contacts		
• at DC / maximum	0.1 A	
supply voltage, current consumption, power loss		
product component / connection for redundant voltage supply	Yes	
type of voltage / 1 / of the supply voltage	DC	
<ul><li>supply voltage / 1 / rated value</li></ul>	24 V	
<ul><li>power loss [W] / 1 / rated value</li></ul>	3 W	
<ul> <li>consumed current / 1 / at rated supply voltage / maximum</li> </ul>	0.25 A	
<ul><li>supply voltage / 1 / rated value</li></ul>	9.6 31.2 V	
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	4-pole terminal block	
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes	
fuse protection type / 1 / at input for supply voltage	2.5 A / 125 V	
ambient conditions		
ambient temperature		
during operation	-40 +70 °C	
<ul> <li>during storage</li> </ul>	-40 +85 °C	
during transport	-40 +85 °C	
relative humidity		
<ul> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %	
protection class IP	IP20	
design, dimensions and weights		

design	compact
width	60 mm
height	147 mm
depth	125 mm
net weight	0.475 kg
material / of the enclosure	Polycarbonate (PC-GF10)
fastening method	
<ul> <li>35 mm top hat DIN rail mounting</li> </ul>	Yes
wall mounting	Yes
S7-300 rail mounting	Yes
S7-1500 rail mounting	Yes
product features, product functions, product components / general	
number of automatically learnable MAC addresses	2048
product functions / management, configuration, engineering	
product function	
<ul> <li>multiport mirroring</li> </ul>	No
• CoS	Yes
product function / switch-managed	No
product functions / redundancy	
product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
standards, specifications, approvals	
standard	
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
for emitted interference	EN 61000-6-4 (Class B)
reference code	
• according to IEC 81346-2	KF
<ul> <li>according to IEC 81346-2:2019</li> </ul>	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010
• from CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T, Class 1 / Zone 2 / Group IIC / T
certificate of suitability	
<ul> <li>CCC / for hazardous zone according to GB standard</li> </ul>	Yes
CCC / for hazardous zone according to GB standard / as	Ex nA IIC T4 Gc
marking	
standards, specifications, approvals / other	
laser protection class	LED Class 1
certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
KC approval	Yes
• E1 approval	Yes
<ul> <li>EC Declaration of Conformity EN 61010, IEC 61010-1, UL 61010A-1</li> </ul>	Yes
standards, specifications, approvals / marine classification	
Marine classification association	
<ul> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	Yes
<ul> <li>French marine classification society (BV)</li> </ul>	Yes
DNV GL	Yes
<ul> <li>Korean Register of Shipping (KRS)</li> </ul>	Yes
<ul> <li>Lloyds Register of Shipping (LRS)</li> </ul>	Yes
Polski Rejestr Statkow (PRS)	Yes
Royal Institution of Naval Architects (RINA)	Yes
further information / internet links	
internet link	
to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

http://www.siemens.com/simatic-net https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

## security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

5/27/2023