SIEMENS

Data sheet

6GK5615-0AA00-2AA2

product type designation



S615

SCALANCE S615 LAN router; for protection of devices/networks in automation technology and for protection of industrial communication by means of VPN and firewall; Further functions: address conversion (NAT/NAPT), connection to SINEMA RC, 5-port switch, 1x dig. input, 1x digital output.

transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	5
number of electrical connections	
for power supply	1
 for redundant voltage supply 	1
type of electrical connection	
for power supply	5-pole terminal block
design of the removable storage / C-PLUG	Yes
signal inputs/outputs	
number of electrical connections	
 for digital input signals 	1
for digital output signals	1
type of electrical connection	
 for digital input signals 	2-pole terminal block
 for digital output signals 	2-pole terminal block
supply voltage, current consumption, power loss	
supply voltage / 1 / rated value	24 V
power loss [W] / 1 / rated value	4 W
supply voltage / 1 / rated value	10.8 28.8 V
consumed current	
at DC / at 24 V / typical	0.2 A
product component / 1 / fusing at power supply input	Yes
fuse protection type / 1 / at input for supply voltage	Non-replaceable melting fuse (F 2 A5 / 32 V)
ambient conditions	
ambient temperature	
 during operation 	-40 +70 °C
 during storage 	-40 +80 °C
during transport	-40 +80 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
width	35 mm
height	147 mm
depth	127 mm

net weight	0.4 kg
fastening method	
 35 mm top hat DIN rail mounting 	Yes
S7-300 rail mounting	Yes
S7-1500 rail mounting	Yes
product functions / management, configuration, engineering	
product function	
• CLI	Yes
 web-based management 	Yes
MIB support	Yes
protocol / is supported	
• HTTP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
type of configuration	Web Based Management, CLI, SNMP, SCT (Configuration support for certificate generation)
product functions / diagnostics	
product function	
 SysLog 	Yes
 packet filter log 	Yes
• audit log	Yes
• system log	Yes
product functions / DHCP	
product function	
DHCP client	Yes
DHCP server - internal network	Yes
product functions / routing	
product function / static IP routing	Yes
product functions / security	
firewall version	stateful inspection
product function / with VPN connection	IPsec, OpenVPN (as client for SINEMA RC)
type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
type of hashing algorithms / with VPN connection	MD5, SHA-1, SHA-256, SHA-384, SHA-512
number of possible connections / with VPN connection	20
product function	
password protection	Yes
bandwidth limitation	No
NAT/NAPT	Yes
product functions / time	
protocol / is supported / NTP	Yes
product component / hardware real time clock	Yes
product feature / hardware real time clock w. battery backup	No
standards, specifications, approvals	
standard	
for emitted interference	EN 61000-6-4
for interference immunity	EN 61000-6-2
certificate of suitability	ATEX, EMC, RoHS
CE marking	Yes
standards, specifications, approvals / marine classification	
Marine classification association	
	Yes
 American Bureau of Shipping Europe Ltd. (ABS) 	
Eropoh marino algorification assist: (D) ()	
French marine classification society (BV) PNN/ Cl	Yes
• DNV GL	Yes
DNV GLKorean Register of Shipping (KRS)	Yes Yes
DNV GLKorean Register of Shipping (KRS)Lloyds Register of Shipping (LRS)	Yes Yes Yes
 DNV GL Korean Register of Shipping (KRS) Lloyds Register of Shipping (LRS) Nippon Kaiji Kyokai (NK) 	Yes Yes Yes Yes
DNV GLKorean Register of Shipping (KRS)Lloyds Register of Shipping (LRS)	Yes Yes Yes

standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-15, EN 60079-0, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
• as marking	Ex nA IIC T4 Gc
accessories	
product extension / optional / C-PLUG	Yes
product extension / optional / KEY-PLUG	Yes
accessories	optional KEY-PLUG
further information / internet links	
internet link	
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
to website: CAx-Download-Manager	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

5/28/2023